







ALL Profiles/Frames are 21mm thick and extruded from high tensile FURNITURE grade ALUMINIUM. Finishes are descriptive only.

	50/01 mm BOX**	50/08 mm BOX	50/19 mm BOX	50/31 mm BOX	50/43 mm BOX	50/50 mm BOX
						

Clear Anodised	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Brushed Stainless	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Champagne Gloss	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Black Gloss	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
Black Matt	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>

**Inserts\*\***  
All Inserts are suitable for all profiles except the 50/01. Compatible inserts for 50/01 can be up to 4.5mm in thickness, must be opaque and, if the insert is glass, must have flat polished edges. Inserts for 50/01 are adhesive fixed only. For more information see Insert Specifications.

**Handles**  
No handles are required when Full Overlay Touch to Open Hinges are used. Clear anodised integrated handles are available.

**Handle Positioning**  
Handle holes can be pre-drilled in suitable inserts - the holes align with the centre of the profile/frame. For handles located in inserts, see Aluminum Framed Doors Insert Spec's - must provide drawing of hole positions required.

**Hinged Doors**  
Supplied with recommended number of hinge holes determined by height, width & weight of the door. 35 mm cup hole only for all hinge brands.

**Suitable Hinges**  
All Profiles/Frames are suitable for all cup hinges. Cup Hinge 35 mm hole centre must be no less than 78mm from the corners of the door.

**Strut Door HK-XS**  
Supplied with 35 mm hinge holes. Minimum internal carcass HEIGHT for strut is 200 mm.

**Spring Flap Door HK [TIP-ON available]**  
Minimum internal carcass DEPTH for hardware is 278 mm - Minimum internal carcass HEIGHT is 175 mm. Note: each mechanism is 35 mm thick.

**Microwave Door HL**  
Minimum internal carcass HEIGHT for microwave door is 263 mm. Note: each mechanism is 35 mm thick.

**Up & Over Door HS**  
Note: each mechanism is 35 mm thick.

**Lift Up Bi-Fold HF**  
**ORDER by ENTERING OVERALL HEIGHT AND WIDTH DIMENSIONS of the 2 DOORS REQUIRED.**  
Supplied with 2 off 35 mm hinge holes for doors up to 1200 mm wide. From 1200 mm to 1800 mm an extra 35 mm hinge hole is drilled.  
Note: each mechanism is 35 mm thick.

**Drawer Fronts**  
All profiles/frames are suitable for this application.

**Bottom-Running Sliding Doors for Cabinets only**  
**ORDER by ENTERING INTERNAL CARCASS HEIGHT AND WIDTH DIMENSIONS.**  
Bottom-running Sliding Doors supplied with aluminium top & bottom track. Each door fitted with Hettich Slideline 55 - 2 top guides and 2 bottom runners. Track available in surface mount or recessed options and, also, either clear anodised or white powder coated aluminium finishes.

**Overlay Sliding Doors Bi-Fold [1 pair] for Cabinets only**  
**ORDER by ENTERING OVERALL HEIGHT AND WIDTH DIMENSIONS of the 2 DOORS REQUIRED.**  
Overlay Sliding Bi-fold Doors are supplied with hinge drilling to suit your hardware selection. If 2 pair are required, order 1 left hand door & 1 right hand door. - Hardware drilling diagram must be supplied.

**Door weights**  
To enable calculation of required hardware, individual door weights are calculated and shown on the "Preview Door Costing" section of the website.

**Hardware**  
**AS OUR RELATIONSHIP WITH HARDWARE DISTRIBUTORS HAS CHANGED, WE ARE UNABLE TO SOURCE DIRECT SUPPLY OF BLUM & AVENTOS PRODUCTS.**  
We will continue to supply the Hettich Slideline 55 for bottom running sliding doors.

**See Luxul Specifications for minimum and maximum door sizes available.**

**\*\* See Insert Specifications. Customers can supply insert material - thickness limited to 5 mm for all profiles except 50/01.**

235 Orchard Road, Richlands Q 4077  
PO Box 3687, Mt Ommaney Q 4074  
Tel: 1300 560 042 Fax: 1300 560 069  
Email: sales@luxul.com.au  
www.luxul.com.au

