

Office Use Only
Int. Ref.
No of pages.

☐ QUOTE ☐ ORDER

Customer Name	Cust Order NO
Delivery Address	Order Date Date Req
Phone Mobile	Fax Number
	Email

o Luxul Frameless Cabinet Doors are manufactured using 16 mm substrate backed with 1.2 mm Laminate liner, cut to suit the required door size and edge-banded. The 3mm mirror is then pressed onto the board - an exact fit - to each and every edge. Suitable primarily for Shaving Cabinet Doors.

Step 1 : Enter Door details.						Supply Qty, Size & hinge handing [from the front].	
Enter hinge pattern [Blum or Hettich] Or 35 mm hole only						Special Instructions, Hinge Drilling Positions or Drawing	
Hinge Drilling	Quantity	Height [mm]	Width [mm]	Left	Right		
<i>Example 35mm hole only</i>	<u>1</u>	<u>900</u>	<u>480</u>	✓			
							Mirror Cabinet Door max height is 1250 mm - max width is 700 mm - max area is 0.845 m².

Step 2 : Select Substrate

Only 16 mm particleboard with choice of:-

☐ 1.2 mm white laminate liner backing.

☐ 1.2 mm black laminate liner backing.

Step 3 : Select Substrate Edgebanding

Brand _____ Finish _____

Colour _____

☐ Edgeband will be supplied by client.

- o Knock-in hinges are not recommended

Note:- Hinge holes or patterns charged at \$2.00 each.

Note:- for each project order or group of orders exceeding a quantity of 100 units of Goods, special conditions apply in accordance with clause 3.2 of our Terms & Conditions of Sale.

- o 5 year Warranty for mirror doors

If insufficient space - supply additional drawings, etc. and email or FAX with this order. Please note number of pages FAXED in top right hand corner box.

	200	300	400	500	600	700
300	2	2	2	2	n/a	n/a
400	2	2	2	2	n/a	n/a
500	2	2	2	2	3	3
600	2	2	2	2	3	3
700	3	3	3	3	3	3
800	3	3	3	3	3	3
900	3	3	3	3	3	3
1000	3	3	3	3	3	4
1100	3	3	3	3	3	4
1200	3	3	3	3	4	4
1250	3	3	3	3	4	4

Humidity is the cause of doors bowing. Central hinges will assist in stabilising the doors except in extreme highs and lows of humidity.
In the grid to the left, the number of hinges shown is the minimum number of hinges required to meet Luxul warranty conditions.
The hinge spacing must be as equi-distant as possible.

If **Undrilled Panels** are ordered, supply will be on the condition that, if the purchaser will be hinging those panels, the purchaser will adhere to the Recommended Number of Hinges Grid. Failure to do so will void the warranty.

All hinge holes require sealing [PVA].

The hinge spacing must be as equi-distant as possible.

- The sale is subject to the Terms & Conditions available on our website www.luxul.com.au
- By submitting this order you agree that you have read and understood the Terms & Conditions.
- **ALL** orders cancellations or changes to sizing, materials or colour **can't be accepted** after 9am on the following **BUSINESS** day.
 - LIMITED WARRANTY of 5 years on manufacturing defects and is limited to repair or replacement only.
 - Proof of delivery is required. There must be a person present at the delivery address you have provided, during normal business hours, to sign for the goods.
 - This order form is a legal document & the information contained here-in will take precedence over any other document.

Client Signature..... **Contact Name [print]**.....

For Quote or Order FAX to 1300 560 069 or email form to sales@luxul.com.au

For Sales Enquiries 1300 560 042

Online ordering is available at <http://www.luxul.com.au>